## NSN 4810-01-430-7345

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-430-7345

#### Thread Direction:

Right-hand all ends

### **Flow Control Device:**

Disk

#### Flow Control Device Normal Operation Position:

Open

#### Maximum Operating Temp:

180.0 degrees fahrenheit single response

#### **End Application:**

Engine, aircraft, f1

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### **Current Rating In Amps:**

0.260

#### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe all ends

#### **Mounting Position:**

Horizontal or vertical

#### Maximum Operating Pressure:

125.0 pounds per square inch single response

#### **Thread Size:**

0.250 inches all ends

#### Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

#### Frequency In Hertz:

60.0

## Material:

Rubber butadiene-acrylonitrile class nbr seat

## Media For Which Designed:

Air 1st response

## Style Designator:

Err-090

## Thread Series Designator:

Nptf all ends

## Furnished Items And Quantity:

1 cap

## Shelf Life:

N/a

# NSN 4810-01-430-7345

Solenoid Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

