NSN 4810-01-433-2647

Solenoid Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-01-433-2647

| Flow Control Device: |
|--|
| Disk |
| Flow Control Device Normal Operation Position: |
| Closed |
| Bolt Hole Quantity: |
| 4 all ends |
| Maximum Operating Temp: |
| 185.0 degrees fahrenheit single response |
| End Application: |
| Mars class afs |
| Current Rating In Amps: |
| 0.200 |
| Valve Operation Method: |
| Solenoid |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal |
| Valve Size: |
| 1.500 inches |
| Voltage In Volts And Current Type: |
| 60.0 ac |
| Outside Diameter: |
| 6.125 inches all ends |
| Face To Face Distance: |
| 9.000 inches |
| Thickness: |
| 0.812 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 4.500 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Steel comp 316 |
| |

NSN 4810-01-433-2647 Solenoid Valve - Page 2 of 2



| Material Specification: |
|---|
| Astm a351 cf8m assn standard single material response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A046b0