## NSN 4810-01-435-0536

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-435-0536 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 1.000 inches Flow Control Device: Diaphragm Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **End Application:** Strategic sealift conversion ships class **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.260 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 1.000 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single **Special Features:** Explosion proof Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr seat Media For Which Designed: Water-oil-gas single response **Style Designator:** 

Material:
Rubber butadiene-acrylonitrile class nbr seat

Media For Which Designed:
Water-oil-gas single response

Style Designator:
Err-090

Thread Series Designator:
Npt all ends

## NSN 4810-01-435-0536

Solenoid Valve - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0