## NSN 4810-01-439-3433

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-439-3433

#### **Thread Direction:**

Right-hand all ends

## **Flow Control Device:**

Disk

## Flow Control Device Normal Operation Position:

Closed

## Maximum Operating Temp:

212.0 degrees fahrenheit single response

#### **End Application:**

Strategic sealift conversion ships class

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### **Current Rating In Amps:**

0.260

#### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe all ends

#### **Mounting Position:**

Horizontal or vertical

#### Maximum Operating Pressure:

110.0 pounds per square inch single response

#### **Thread Size:**

0.750 inches all ends

#### Voltage In Volts And Current Type:

115.0 ac

#### Phase:

Single

#### **Special Features:**

Explosion-proof type

#### **Frequency In Hertz:**

60.0

## Material:

Copper alloy body

## Media For Which Designed:

Oil 2nd response

## Style Designator:

Err-090

## Thread Series Designator:

Nptf all ends

## Shelf Life:

N/a

# NSN 4810-01-439-3433

Solenoid Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

