## NSN 4810-01-444-0995

Linear Hydraulic-pneumatic Actuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-444-0995 **Body Material: Brass Mounting Provision:** Threaded mounting holes **Bore Diameter:** 1.377 inches **Longest Horizontal Distance Between Mounting Centers:** 3.750 inches **Longest Vertical Distance Between Mounting Centers:** 3.750 inches **End Application:** Seawolf class ssn **Mounting Facility Thread Class:** 2b **Mounting Facility Thread Direction:** Right-hand **Mounting Provision Arrangement Style:** Four hole square **Mounting Facility Thread Series Designator:** Unc **Mounting Facility Thread Diameter:** 0.625 inches Mounting Facility Thready Qty Per Inch (tpi): **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Internal threaded First Piston Rod End Thread Series Designator: First Piston Rod End Thread Diameter: 1.250 inches First Piston Rod End Thready Qty Per Inch (tpi): 12 First Piston Rod End Thread Class: 2b First Piston Rod End Thread Direction:

Right-hand

**Mounting Type And Location:** 

Lug center section

## NSN 4810-01-444-0995

Linear Hydraulic-pneumatic Actuator - Page 2 of 2



Mounting Facility I nread Lengti
0.940 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:

A34200