

View Online at <https://aerobasegroup.com/nsn/4810-01-444-6752>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

12 all ends

Maximum Operating Temp:

1100.0 degrees fahrenheit single response

Minimum Operating Temp:

-20.0 degrees fahrenheit

End Application:

Strategic sealift conversion ships class

Valve Operation Method:

Electric motor

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Valve Size:

6.000 inches

Maximum Operating Pressure:

290.0 pounds per square inch single response

Outside Diameter:

15.000 inches all ends

Face To Face Distance:

24.000 inches

Thickness:

2.187 inches all ends

Bolt Hole Diameter:

1.250 inches all ends

Bolt Circle Diameter:

12.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

8.500 inches all ends

Special Features:

With motor operator

Material:

Steel uns k11572 flow control device

Material Specification:

Astm a276 410 assn standard single material response stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0