

View Online at <https://aerobasegroup.com/nsn/4810-01-445-8969>

**Thread Class:**

3b

**End Connection Quantity:**

4

**Valve Discharge Flow Rate:**

6.0 gallons per minute

**End Application:**

Coast guard hh65-a hoist control system

**Current Rating In Amps:**

0.02

**Valve Operation Method:**

Solenoid and manual

**Connection Type:**

Threaded internal boss

**Features Provided:**

Manual override

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

0.740 inches

**Body Material:**

Steel and aluminum alloy a356.0

**Maximum Operating Temperature And Media For Which Designed:**

200.0 degrees fahrenheit hydraulic fluid, petroleum base

**Voltage In Volts And Current Type:**

7.6 dc

**Spool Position Quantity:**

6

**Spool Quantity:**

3

**Special Features:**

This hoist control valve is a 2- stage, 4 way, electrohydraulic flow control valve incorporating a pressure regulator valve to maintain constant flow with varying loads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A506h0