## NSN 4810-01-446-2508

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-446-2508

## Thread Direction:

Right-hand all ends

## **Flow Control Device:**

Piston

## Flow Control Device Normal Operation Position:

Open

## Maximum Operating Temp:

212.0 degrees fahrenheit single response

#### **End Application:**

Mars class afs

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### **Current Rating In Amps:**

0.500

#### Valve Operation Method:

Solenoid

#### **Connection Type:**

Threaded internal pipe all ends

## Mounting Position:

Horizontal

### Maximum Operating Pressure:

300.0 pounds per square inch single response

#### Thread Size:

0.500 inches all ends

#### Voltage In Volts And Current Type:

120.0 ac

#### Phase:

Single

## Frequency In Hertz:

60.0

#### Material:

Steel comp 303 seat

#### Media For Which Designed:

Air 2nd response

#### Style Designator:

Err-090

#### **Thread Series Designator:**

Npt all ends

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 4810-01-446-2508

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

