NSN 4810-01-456-7552

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-456-7552

view Offline at https://aerobasegroup.com/nsi//4010-01-450-7552
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
194.0 degrees fahrenheit single response
Minimum Operating Temp:
-22.0 degrees fahrenheit
End Application:
Winch assembly; weapon code ja, nimitz class cvn
Connection Style:
G46d plain (screw-in cartridge) all ends
Current Rating In Amps:
1.160
Valve Operation Method:
Solenoid
Connection Type:
Threaded cartridge all ends
Mounting Position:
Horizontal or vertical
Valve Size:
0.375 inches
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.875 inches all ends
Voltage In Volts And Current Type:
12.0 dc
Special Features:
Symmetrical coil can be reversed, requires no o-rings, is hermertically sealed and is waterproof
Material:
Steel body
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Err-090
Thread Series Designator:

Unf all ends

NSN 4810-01-456-7552

Solenoid Valve - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0