NSN 4810-01-466-1922

Gate Valve - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/4810-01-466-1922

view Offilite at https://aerobasegroup.com/nsi//4010-01-400-1322
Flange Diameter:
10.125 inches
Bonnet Type:
Packing retaining
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
12
Valve Operation Method:
Electric motor or manual
Connection Type:
Flange, round w/holes
Valve Size:
6.000 inches
Maximum Operating Pressure And Media For Which Designed:
250.0 pounds per square inch water-oil-gas
Stem Type:
Nonrising
Maximum Operating Tempurature And Media For Which Designed:
400.0 degrees fahrenheit water-oil-gas
Face To Face Distance:
8.062 inches
Flange Face Design:
Plain
Inlet Relationship With Outlet:
Identical
Pressure Class:
250.0 pounds per square inch
Material:
Nickel alloy seat
Material Specification:
Qq-n-288 compa federal specification single material response seat
Test Data Document:
53711-253973 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Furnished Items And Quantity:
1 gasket and 1 handwheel and 31 nut
Specification Data:
53711-mil-v-1189/mod cl2 government specification
Departure From Cited Document:
As modified for electric motor operation
Shelf Life:

NSN 4810-01-466-1922

Gate Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A500a0