

View Online at <https://aerobasegroup.com/nsn/4810-01-468-5130>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

248.0 degrees fahrenheit single response

**Connection Style:**

G46a plain (tube) all ends

**Current Rating In Amps:**

0.750

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded cartridge all ends

**Mounting Position:**

Vertical

**Thready Qty Per Inch (tpi):**

14 all ends

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.875 inches all ends

**Voltage In Volts And Current Type:**

24.0 dc

**Product Name:**

2-way, poppet type, normally closed solenoid valve

**Special Features:**

Din 43650 connector

**Material:**

Rubber butadiene-acrylonitrile class nbr packing

**Media For Which Designed:**

Hydraulic fluid, mineral base single response

**Surface Treatment:**

Anodize

**Style Designator:**

Err-090

**Thread Series Designator:**

Unj all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0