

View Online at <https://aerobasegroup.com/nsn/4810-01-480-3988>

**Thread Direction:**

Right-hand all ends

**Flow Control Device Normal Operation Position:**

Open

**Bolt Hole Quantity:**

2 all ends

**Maximum Operating Temp:**

200.0 degrees fahrenheit 2nd response

**Minimum Operating Temp:**

-50.0 degrees fahrenheit

**End Application:**

2320-01-465-2174

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Width:**

3.190 inches all ends

**Length:**

3.940 inches all ends

**Current Rating In Amps:**

0.020

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal

**Power Drive Operating Pressure:**

150.0 pounds per square inch

**Inlet/outlet Operating Pressure Differential:**

150.0 pounds per square inch

**Thread Size:**

0.250 inches all ends

**Voltage In Volts And Current Type:**

24.0 dc

**Thickness:**

1.000 inches all ends

**Bolt Hole Diameter:**

0.166 inches all ends

**Center To Center Distance Between Bolt Holes Along Length:**

3.688 inches all ends

**Center To Center Distance:**

3.940 inches

**Product Name:**

Valve, solenoid 25ta, 24vdc

**Material:**

Stainless steel body lining

**Surface Treatment:**

Anodize

**Style Designator:**

Err-090

**Thread Series Designator:**

Nptf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0