

View Online at <https://aerobasegroup.com/nsn/4810-01-480-3988>

Thread Direction:

Right-hand all ends

Flow Control Device Normal Operation Position:

Open

Bolt Hole Quantity:

2 all ends

Maximum Operating Temp:

200.0 degrees fahrenheit 2nd response

Minimum Operating Temp:

-50.0 degrees fahrenheit

End Application:

2320-01-465-2174

Connection Style:

G9 plain, optional en (pipe) all ends

Width:

3.190 inches all ends

Length:

3.940 inches all ends

Current Rating In Amps:

0.020

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal

Power Drive Operating Pressure:

150.0 pounds per square inch

Inlet/outlet Operating Pressure Differential:

150.0 pounds per square inch

Thread Size:

0.250 inches all ends

Voltage In Volts And Current Type:

24.0 dc

Thickness:

1.000 inches all ends

Bolt Hole Diameter:

0.166 inches all ends

Center To Center Distance Between Bolt Holes Along Length:

3.688 inches all ends

Center To Center Distance:

3.940 inches

Product Name:

Valve, solenoid 25ta, 24vdc

Material:

Stainless steel body lining

Surface Treatment:

Anodize

Style Designator:

Err-090

Thread Series Designator:

Nptf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0