## NSN 4810-01-487-1160

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-487-1160

| Pipe Size Accommodated:  |
|--|
| 3.000 inches 3rd end   |
| Flow Control Device:   |
| Disk   |
| Bolt Hole Quantity:  |
| 6 all ends   |
| Connection Style:  |
| Socket 1st end   |
| Valve Operation Method:  |
| Solenoid   |
| Flange Shape:  |
| Round with holes all ends  |
| Connection Type:   |
| Unthreaded internal pipe 3rd end   |
| Maximum Operating Pressure:  |
| 150.0 pounds per square inch single response                             |
| Outside Diameter:  |
| 6.125 inches all ends  |
| Thickness:   |
| 0.500 inches all ends  |
| Bolt Hole Diameter:  |
| 0.680 inches 3rd end   |
| Bolt Circle Diameter:  |
| 5.750 inches 3rd end   |
| Flange Face Design:  |
| Raised straight all ends   |
| Raised Face Height:  |
| 0.006 inches all ends  |
| Material:  |
| Rubber flow control device   |
| Material Specification:  |
| Qq-n-281 class a or b military specification all material responses seat |
| Media For Which Designed:  |
| Water, fresh single response   |
| Style Designator:  |
| Err-090  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

Yes - demil/mli

## NSN 4810-01-487-1160

Solenoid Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-g-22050 spec.