

View Online at <https://aerobasegroup.com/nsn/4810-01-494-2496>

**Flow Control Device:**

Spool

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-25.0 degrees fahrenheit

**Current Rating In Amps:**

0.230

**Valve Operation Method:**

Solenoid

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

110.0 ac and 120.0 ac

**Product Name:**

Two-position, 2-way, spool-type, solenoid operated directional control valve with viton seals and aluminum body

**Phase:**

Single

**Special Features:**

Valve body has 3/4"-16 unf-2b threaded cavity with 0.625" diameter seat to accommodate screw-in cartridge which is included along with the coil; this valve has viton seals and an aluminum body with 3 sae-4 sized ports; has 25 watt coil for heavy duty application; coil termination is 1/2-inch nptf conduit connector with 24-inch wires, class h leads

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum body

**Media For Which Designed:**

Oil, hydraulic single response

**Style Designator:**

Err-090

**Supplementary Features:**

THIS-SO-LEN-OIDV

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0