

View Online at <https://aerobasegroup.com/nsn/4810-01-495-4182>

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Open

End Application:

Shelter, nonexpandable, light weight, multipurpose; nsn 5411-01-436-3326.

Connection Style:

Socket (tube) all ends

Valve Operation Method:

Solenoid

Connection Type:

Unthreaded external tube all ends

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

275.0 pounds per square inch

Maximum Operating Pressure:

500.0 pounds per square inch single response

Voltage In Volts And Current Type:

208.0 ac and 240.0 ac

Outside Diameter Tube Accommodated:

0.500 inches all ends

Product Name:

Solenoid valve

Special Features:

Can be used with most commercially available cfc, hcfc, & hfc refrigerants, call cage for confirmation; coil kit p/n omkc-2 included; end connections are untreated external and unthreaded internal tube on all ends and will accommodate 1/2 in. Outside diameter tube or a 5/8 in. Inside diameter tube.

Frequency In Hertz:

50.0 and 60.0

Material:

Stainless steel stem

Media For Which Designed:

Refrigerant 12 1st response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0