

View Online at <https://aerobasegroup.com/nsn/4810-01-499-4558>

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Closed

**Connection Style:**

Socket (tube) all ends

**Current Rating In Amps:**

0.210

**Valve Operation Method:**

Solenoid

**Connection Type:**

Unthreaded internal tube all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

300.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

120.0 ac

**Outside Diameter Tube Accommodated:**

0.375 inches all ends

**Product Name:**

Solenoid valve

**Phase:**

Single

**Special Features:**

Brass body; renewable cres disk; renewable polytetrafluoroethylene seat; solder or brazed tubing (swaged) end connections; end to end/face to face 4.31 in.; r134 refrigerant; one-way flow direction; 0.21 amps continuous duty; level iii valve, do not install l1/ss service

**Frequency In Hertz:**

60.0

**Material:**

Plastic polytetrafluoroethylene flow control device

**Style Designator:**

C7 straight through note: to be used for valve bodies of separable sections.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0