

View Online at <https://aerobasegroup.com/nsn/4810-01-501-6084>

**Pipe Size Accommodated:**

0.250 inches all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

200.0 degrees fahrenheit single response

**End Application:**

W/s nimitz class cvn

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal

**Thready Qty Per Inch (tpi):**

18 all ends

**Inlet/outlet Operating Pressure Differential:**

150.0 pounds per square inch

**Thread Size:**

0.250 inches all ends

**Voltage In Volts And Current Type:**

120.0 ac

**Product Name:**

3-way direct acting general service solenoid valve

**Special Features:**

Asco red hat ii molded epoxy solenoid includes mounting bracket (indicated by mb suffix to p/n). 3 wire leads, 18 inches long. Similar to 4810-00-828-2027 which does not have a mounting bracket included.

**Frequency In Hertz:**

60.0

**Material:**

Rubber butadiene-acrylonitrile class nbr flow control device or plastic polyurethane flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Err-090

**Thread Series Designator:**

Npt all ends

**Furnished Items And Quantity:**

1 mounting bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0