

View Online at <https://aerobasegroup.com/nsn/4810-01-501-6084>

Pipe Size Accommodated:

0.250 inches all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

200.0 degrees fahrenheit single response

End Application:

W/s nimitz class cvn

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

18 all ends

Inlet/outlet Operating Pressure Differential:

150.0 pounds per square inch

Thread Size:

0.250 inches all ends

Voltage In Volts And Current Type:

120.0 ac

Product Name:

3-way direct acting general service solenoid valve

Special Features:

Asco red hat ii molded epoxy solenoid includes mounting bracket (indicated by mb suffix to p/n). 3 wire leads, 18 inches long. Similar to 4810-00-828-2027 which does not have a mounting bracket included.

Frequency In Hertz:

60.0

Material:

Rubber butadiene-acrylonitrile class nbr flow control device or plastic polyurethane flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Furnished Items And Quantity:

1 mounting bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0