

View Online at <https://aerobasegroup.com/nsn/4810-01-503-8733>

Thread Class:

2 all ends

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Closed

Maximum Operating Temp:

353.0 degrees fahrenheit single response

End Application:

Large capacity coolant heating system; kim hotstart mfg. Co., model cl31804-cat-4136.

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

11-1/2 all ends

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

1.500 inches all ends

Voltage In Volts And Current Type:

110.0 ac

Product Name:

Solenoid valve

Special Features:

Csolenoid valve is rated general purpose, hot water/steam with high temp. Pffe seals 2 way, n/c, w/1-1/2 inch. Npt ports, 110 vac. 7000 series 2 way valves. This valve is designed to be multi-poised and so will perform properly when mounted in any position. However, for optimum life and performance, the valve should be mounted vertically upright so as to minimize wear and reduce the possibility of foreign matter accumulating inside the sleeve area.

Material:

Copper alloy body

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A046b0