

View Online at <https://aerobasegroup.com/nsn/4810-01-515-3871>

End Connection Quantity:

3

Valve Discharge Flow Rate:

25.0 gallons per minute

End Application:

2350-01-080-9088

Valve Operation Method:

Hydraulic

Connection Type:

Threaded internal tube

Features Provided:

Bulkhead mounted and spring loaded

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch oil, lubricating, diester base and 3000.0 pounds per square inch hydraulic fluid, petroleum base

Maximum Operating Temperature And Media For Which Designed:

225.0 degrees fahrenheit oil, hydraulic

Product Name:

Directional control valve

Spool Position Quantity:

1

Spool Quantity:

1

Special Features:

Nonblock spool type providing and inlet and an outlet, an integral adjustable relief valve and spring loaded spool; spool travels 5/16 plus/minus 1/16 between positions; relief valve adjustable from 1500 psi through 3000 psi; oper temp is minus 65.0 fahr; length 9.750 inches; width is 5.500 inches; outlet tube sz 0.750 inches and 2 inlet tube sz is 0.630 inches

Furnished Items And Quantity:

1 relief valve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A506h0