

View Online at <https://aerobasegroup.com/nsn/4810-01-516-9412>

Thread Direction:

Right-hand all ends

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

350.0 degrees fahrenheit single response

End Application:

Nha I9668-101-011, u/o mpts (test set)

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Electric motor

Connection Type:

Threaded internal pipe all ends

Mounting Facility:

Panel

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Voltage In Volts And Current Type:

24.0 dc

Product Name:

Shutoff valve

Special Features:

Valve, 3-way, spring return to port 1; actuator material is aluminum; cycle time 1 second; cv factor 0.66 psi; actuator maximum pressure 125 psig; valve shall return to normal position upon loss of actuator pressure; mounting bracket provided as part of the actuator

Material:

Steel comp 316

Media For Which Designed:

Gas, inert single response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0