

View Online at <https://aerobasegroup.com/nsn/4810-01-518-1341>

Pipe Size Accommodated:

3.000 inches all ends

Renewable Seat Ring Type:

Pressed-in

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain (tube) all ends

Current Rating In Amps:

10.000

Valve Operation Method:

Electric motor or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

3.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Voltage In Volts And Current Type:

115.0 ac

Outside Diameter:

6.625 inches all ends

Face To Face Distance:

9.000 inches

Thickness:

0.500 inches all ends

Bolt Hole Diameter:

0.562 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Third Connection Face To Centerline Distance:

4.500 inches

Flange Face Design:

Plain all ends

Phase:

Single

Special Features:

Ball valve iaw mil-v24509, figure 5, 3-way 3-port 90 degrees handle; actuator is p/n 12270-1623-0100-040k iaw dod-v-24657 model ms12q electric actuator, motor iaw mil-m-17059; assembly required to meet mil-s-901c (shock) and mil-std-167-1 (vibration) qualification.

Handwheel assembly (spinner) provided for manual control of valve.

Frequency In Hertz:

60.0

Material:

Plastic polytetrafluoroethylene seat

Material Specification:

Qq-n-281 cl a b d federal specification single material response stem

Media For Which Designed:

Water, salt 1st response

Style Designator:

A11a cross flanged ends

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24509 spec.