## NSN 4810-01-519-7841



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-519-7841 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk Flow Control Device Normal Operation Position: Closed Renewable Seat Ring Type: Pressed-in **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Minimum Operating Temp:** 32.0 degrees fahrenheit **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 5.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 1.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac **Special Features:** Pilot operated slow closing solenoid valve, fci-82-1 class bb, closed when de-energized Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Water, fresh single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4810-01-519-7841

Solenoid Valve - Page 2 of 2



Demi			

No

Fiig:

A046b0