

View Online at <https://aerobasegroup.com/nsn/4810-01-520-8520>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

550.0 degrees fahrenheit single response

End Application:

Main engine gland seal augment

Valve Operation Method:

Hydraulic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Manual override and pressure tight outlet side

Valve Size:

1.500 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Face To Face Distance:

8.688 inches

Flange Face Design:

Raised straight all ends

Product Name:

1-1/2" donsza diaphragm control valve with 55 actuator & h.O.D. & 760e

Material:

Stainless steel seat

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Test Data Document:

Mil-s-901c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Furnished Items And Quantity:

1 handwheel

Specification Or Standard:

1 type and d composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-901 spec.