## NSN 4810-01-521-4589

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-521-4589

**Thread Class:** 16 all ends **Thread Direction:** Right-hand all ends Flow Control Device: Spool Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **End Application:** Ws: an/wld- (v) remote mine hunting system **Connection Style:** G46d plain (screw-in cartridge) all ends **Current Rating In Amps:** 14.000 **Valve Operation Method:** Solenoid **Connection Type:** Threaded cartridge all ends **Mounting Position:** Vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Voltage In Volts And Current Type:** 24.0 dc **Product Name:** Spool type, 4-way valve series dsl084 **Special Features:** Din plug face coil termination; no diode; cartridge only; seal material is nitrile Material: Steel body Media For Which Designed: Oil, hydraulic 1st response **Style Designator:** Err-090 **Thread Series Designator:** 

Unf all ends

## NSN 4810-01-521-4589

Solenoid Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0