# NSN 4810-01-521-4589

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-521-4589

# Thread Class:

16 all ends

**Thread Direction:** 

Right-hand all ends

# Flow Control Device:

Spool

#### Flow Control Device Normal Operation Position:

Open

#### Maximum Operating Temp:

200.0 degrees fahrenheit single response

### Minimum Operating Temp:

-40.0 degrees fahrenheit

### **End Application:**

Ws: an/wld- (v) remote mine hunting system

#### **Connection Style:**

G46d plain (screw-in cartridge) all ends

# Current Rating In Amps:

14.000

### Valve Operation Method:

Solenoid

# **Connection Type:**

Threaded cartridge all ends

# Mounting Position:

Vertical

# Maximum Operating Pressure:

3000.0 pounds per square inch single response

# Thread Size:

0.750 inches all ends

# Voltage In Volts And Current Type:

24.0 dc

#### **Product Name:**

Spool type, 4-way valve series dsl084

#### **Special Features:**

Din plug face coil termination; no diode; cartridge only; seal material is nitrile

#### Material:

Steel body

# Media For Which Designed:

Oil, hydraulic 1st response

# Style Designator:

Err-090

#### **Thread Series Designator:**

Unf all ends

# NSN 4810-01-521-4589

Solenoid Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

