

View Online at <https://aerobasegroup.com/nsn/4810-01-528-4437>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Valve Operation Method:

Air

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing and manual override

Valve Size:

1.000 inches

Power Drive Operating Pressure:

150.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Face To Face Distance:

7.300 inches

Flange Face Design:

Raised straight all ends

Product Name:

Sstg gs augment; inavy: valve, globe p/o 1" 150psi flg stl

Special Features:

Model: mark one; flow rate 550 lbs/hr; throttling globe valve with air operator and logix 3200iq-10-d6-e-04-20-0g-00 positioner

Material:

Steel uns j03002 body

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 electrical connector and 1 filter and 1 handwheel and 1 indicator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0