## NSN 4810-01-528-4503

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-528-4503

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
130.0 degrees fahrenheit single response
End Application:
Uss essex
Valve Operation Method:
Air
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Bonnet packing and manual override
Valve Size:
1.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Face To Face Distance:
5.500 inches
Flange Face Design:
Plain all ends
Product Name:
Sstg jptwell
Special Features:
Model: mark one; flow rate 36000 lbs/hr; globe valve with air operator and logix 3200i1-10-d6-e-01-20-0g-00 positioner with indicator
Material:
Stainless steel stem
Material Specification:
Monel k500 mfr ref single material response seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel and 1 indicator
Shelf Life:

N/a

## NSN 4810-01-528-4503

Globe Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0