NSN 4810-01-530-6179

Butterfly Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-530-6179

Pipe Size Accommodated:
3.000 inches all ends
End Application:
Cvn 77
Current Rating In Amps:
10.000 and 2.000
Valve Operation Method:
Electric motor or manual
Mounting Facility:
Wafer
Features Provided:
Bonnet packing and manual override
Maximum Operating Pressure:
275.0 pounds per square inch single response
Voltage In Volts And Current Type:
440.0 ac
Butterfly Valve Size:
3.000 inches
Product Name:
3" butterfly valve, cl 150 to mil-v-24624 st a tt u with electric/optical actuator
Phase:
Three
Special Features:
Application: jp-5, drain and ballast; 1/4 turn electric optical actuator with hand wheel, mounting kit and associated hardware
Frequency In Hertz:
50.0
Material:
Steel uns j93400 body
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel and 1 indicator
Specification Data:
81349 - mil-v02464 amend 1 government specification
Specification Or Standard:
A style and i type
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4810-01-530-6179

Butterfly Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0