

View Online at <https://aerobasegroup.com/nsn/4810-01-530-6296>

End Application:

Cvn 77

Current Rating In Amps:

0.500

Valve Operation Method:

Electric motor or manual

Features Provided:

Bonnet packing and manual override

Maximum Operating Pressure:

275.0 pounds per square inch single response

Voltage In Volts And Current Type:

440.0 ac

Butterfly Valve Size:

6.000 inches

Product Name:

6" butterfly valve, class 150

Phase:

Three

Special Features:

Application: jp-5; furnished with 1/4 turn electric optical actuator, handwheel and mounting kit.

Frequency In Hertz:

50.0

Material:

Steel uns j93400 body

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Furnished Items And Quantity:

1 indicator and 1 handwheel

Specification Data:

81349 - mil-v-24624 amend 1 government specification

Specification Or Standard:

A style and i type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0