

View Online at <https://aerobasegroup.com/nsn/4810-01-530-6296>

**End Application:**

Cvn 77

**Current Rating In Amps:**

0.500

**Valve Operation Method:**

Electric motor or manual

**Features Provided:**

Bonnet packing and manual override

**Maximum Operating Pressure:**

275.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

440.0 ac

**Butterfly Valve Size:**

6.000 inches

**Product Name:**

6" butterfly valve, class 150

**Phase:**

Three

**Special Features:**

Application: jp-5; furnished with 1/4 turn electric optical actuator, handwheel and mounting kit.

**Frequency In Hertz:**

50.0

**Material:**

Steel uns j93400 body

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Style Designator:**

Err-090

**Test Data Document:**

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Furnished Items And Quantity:**

1 indicator and 1 handwheel

**Specification Data:**

81349 - mil-v-24624 amend 1 government specification

**Specification Or Standard:**

A style and i type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0