

View Online at <https://aerobasegroup.com/nsn/4810-01-530-6431>

End Application:

Cvn 77

Current Rating In Amps:

0.500

Valve Operation Method:

Electric motor or manual

Mounting Facility:

Wafer

Features Provided:

Bonnet packing and manual override

Maximum Operating Pressure:

275.0 pounds per square inch single response

Voltage In Volts And Current Type:

440.0 ac

Butterfly Valve Size:

10.000 inches

Product Name:

10" butterfly valve class 150 to mil-v-24624

Phase:

Three

Special Features:

Application: jp-5; 1/4 turn electric optical actuator with handwheel, mounting kit and hardware

Frequency In Hertz:

50.0

Material:

Steel uns j93400 body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-167 standard (includes industry or association standards, individual manufactureer standards, etc.).

Furnished Items And Quantity:

1 indicator and 1 electrical connector

Specification Data:

81349 - mil-v-24624 amend 1 government specification

Specification Or Standard:

A style and i type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-v-24624 spec.