

View Online at <https://aerobasegroup.com/nsn/4810-01-530-6639>

**End Application:**

Cvn 77

**Current Rating In Amps:**

0.500

**Valve Operation Method:**

Electric motor or manual

**Mounting Facility:**

Wafer

**Features Provided:**

Bonnet packing and manual override

**Maximum Operating Pressure:**

275.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

440.0 ac

**Butterfly Valve Size:**

12.000 inches

**Phase:**

Three

**Special Features:**

Application: firemain; 1/4 turn electric optical actuator with handwheel, mounting kit and hardware; electrical receptacle iaw mil-c-5051e

**Frequency In Hertz:**

50.0

**Material:**

Plastic polytetrafluoroethylene seat

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Err-090

**Test Data Document:**

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-167 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Furnished Items And Quantity:**

1 electrical connector and 1 indicator

**Specification Data:**

81349 - mil-v-24624 amend 1 government specification

**Specification Or Standard:**

A style and iii type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0