NSN 4810-01-532-8833

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-532-8833 **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 125.0 degrees fahrenheit single response **Minimum Operating Temp:** -25.0 degrees fahrenheit **End Application:** Light armored vehicle **Connection Style:** G46d plain (screw-in cartridge) 1st end **Current Rating In Amps:** 1.000 **Valve Operation Method:** Hydraulic **Connection Type:** Threaded cartridge 1st end **Mounting Position:** Vertical **Thread Size:** 0.875 inches 1st end **Voltage In Volts And Current Type:** 24.0 dc **Product Name:** Valve cartridge 2 way Material: Steel body Media For Which Designed: Hydraulic fluid, mineral base single response **Surface Treatment:** Zinc **Style Designator:** Err-090 **Thread Series Designator:** Unf 1st end

N/a

Shelf Life:

NSN 4810-01-532-8833

Solenoid Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0