## NSN 4810-01-533-5314

Butterfly Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-533-5314

| Bolt Hole Quantity:  |
|--|
| 6 all ends   |
| Maximum Operating Temp:  |
| 200.0 degrees fahrenheit 1st response                                  |
| Minimum Operating Temp:  |
| -40.0 degrees fahrenheit   |
| End Application:   |
| R11 refueler truck   |
| Valve Operation Method:  |
| Air  |
| Flange Shape:  |
| Round with holes all ends  |
| Connection Type:   |
| Flange all ends  |
| Maximum Operating Pressure:  |
| 75.0 pounds per square inch single response                            |
| Outside Diameter:  |
| 3.750 inches all ends  |
| Thickness:   |
| 1.125 inches all ends  |
| Bolt Hole Diameter:  |
| 0.438 inches all ends  |
| Flange Face Design:  |
| Plain all ends   |
| Butterfly Valve Size:  |
| 2.000 inches   |
| Product Name:  |
| Wet-r-dry valve  |
| Special Features:  |
| Has been tested to 225 psi and has pin 13226 stamped on the vavle body |
| Material:  |
| Rubber synthetic flow control device                                   |
| Media For Which Designed:  |
| Liquid 1st response  |
| Style Designator:  |
| Err-090  |
| Supplementary Features:  |
| Designed for handling liquid, gaseous or dry products.                 |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

## NSN 4810-01-533-5314

Butterfly Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0