

View Online at <https://aerobasegroup.com/nsn/4810-01-534-7554>

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Open

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Minimum Operating Temp:

32.0 degrees fahrenheit

Connection Style:

G9 plain, optional en (pipe) all ends

Current Rating In Amps:

25.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Product Name:

Pilot operated piston/poppet solenoid valves

Special Features:

pressure for light oil at 300.0 ssu. Is 200.0 psi; for air, inert gas, and water pressure is 300.0 psi; ambient temperature range 32.0 to 125.0 degrees f; must specify voltage requirements when ordering; rated for 10.1 watts; 2 mounting holes 0.340 inches diameter; offset flow design with 2 openings opposite each other; 3 openings - pressure, cyl. A, and cyl. B pipe size 0.375 inch diameter; remaining exhaust opening 0.500 inch diameter pipe size; height 4.680 inches; width 6.060 inches; length 3.180 inches; dual solenoid design; explosion proof and watertight

Frequency In Hertz:

50.0 and 60.0

Material:

Copper alloy body

Media For Which Designed:

Water-oil-gas single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0