

View Online at <https://aerobasegroup.com/nsn/4810-01-534-7554>

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Open

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**Minimum Operating Temp:**

32.0 degrees fahrenheit

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Current Rating In Amps:**

25.000

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal or vertical

**Product Name:**

Pilot operated piston/poppet solenoid valves

**Special Features:**

pressure for light oil at 300.0 ssu. Is 200.0 psi; for air, inert gas, and water pressure is 300.0 psi; ambient temperature range 32.0 to 125.0 degrees f; must specify voltage requirements when ordering; rated for 10.1 watts; 2 mounting holes 0.340 inches diameter; offset flow design with 2 openings opposite each other; 3 openings - pressure, cyl. A, and cyl. B pipe size 0.375 inch diameter; remaining exhaust opening 0.500 inch diameter pipe size; height 4.680 inches; width 6.060 inches; length 3.180 inches; dual solenoid design; explosion proof and watertight

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Copper alloy body

**Media For Which Designed:**

Water-oil-gas single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0