NSN 4810-01-538-5507

Rotary Electro-mechanical Actuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-538-5507 **Terminal Type:** Wiring harness assembly modbus rtu **Tempurature Rating:** -29.0 degrees celsius and 65.0 degrees celsius **Current Type:** Ac **Body Length:** 9.130 inches **Body Width:** 8.750 inches **Body Height:** 11.500 inches **Environmental Protection:** Submersible **Operating Speed At Rated Capacity In Rpm: End Application:** Lcs1 **Drive Type:** Gear **Duty Cycle:** Continuous **Output Drive Torque Rating:** 400.0 inch-pounds **Limit Switch Control:** Included **Manual Override:** Included **Mounting Facility:** Mounting flanges **Product Name:**

Quarter-turn electric actuator

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Torque limiter assembly p/n 6120-015-000; with fold-up spinner handwheel

Frequency In Hertz:

60.0

Test Data Document:

Mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And mil-std-167 standard (includes industry or appointing standards, individual manufactureer standards, etc.)

NSN 4810-01-538-5507

Rotary Electro-mechanical Actuator - Page 2 of 2



S	pe	cifi	cati	ion	Data:

81349 - mil-v-24657 government specification

Specification Or Standard:

li type and 1 class and 1 service

Departure From Cited Document:

As modified by avondale drawing 06-017a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A30500

Mil-std (military Standard):

Mil-s-901 spec.