

View Online at <https://aerobasegroup.com/nsn/4810-01-538-9055>

**Current Type:**

Ac

**End Application:**

On-off, fail safe control of air damper in hvac systems

**Shaft Rotation Direction:**

Clockwise

**Manual Override:**

Included

**Angular Shaft Rotation:**

Adjustable

**Voltage In Volts:**

120.0

**Special Features:**

Power supply: 120 vac +/- 10 pct., 50/60 hz; power consumption: running 6w, holding 2.3w; transformer sizing: 10va; electrical connection: 3ft. 18ga, appliance cable: 1/2in. Conduit connector; electrical protection: double insulated; overload protection: electronic throughout: -5 deg. To 90 deg. Rotation; 95 deg. Angle of rotation; torque: 133 in.Lb. (nm) constant; direction or rotation: spring return can be selected by cw/cww mounting; visual position indicator: -5 deg. To 90 deg.; manual override: 3mm hex crank; auxiliary switches: 2 single pole double throw (spdt) 7a (25a) at 250 vac, ul listed; running time: 150 sec. Constant, independent of load, spring return less than 20 sec.; 5 to 95 pct. Rh non-condensing; -22 deg. F. To +122 deg. F. (-30 c. To +50 c.) ambient temp.; -40 deg. F. To +176 deg. F. (-40 deg. C. To +80 deg. C.) storage temp.; zinc coated steel housing, nema type 2

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A30500