

View Online at <https://aerobasegroup.com/nsn/4810-01-539-8588>

Flow Control Device:

Stem

Bonnet Type:

Packing retaining

Maximum Operating Temp:

150.0 degrees fahrenheit single response

End Application:

New construction lcs1

Valve Operation Method:

Air

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Power Drive Operating Pressure:

250.0 pounds per square inch

Maximum Operating Pressure:

285.0 pounds per square inch single response

Face To Face Distance:

10.000 inches

Product Name:

Two-way, reciprocating steel body globe valve with pneumatic/electrical actuator; inavy valve, diaphragm control

Special Features:

Application: inlet back pressure regulating/40 psi inlet; flanges iaw asme 16.5 150 lb.; disassembly distance 4"; actuator has 1/4" fpt air connection, 250 psi max.; no manual over ride; cv 45; valve travel 0.75"; type 5800 valve p/n d3230930, actuator p/n d3378425

Material:

Steel uns j03002 body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0