

View Online at <https://aerobasegroup.com/nsn/4810-01-539-8588>

**Flow Control Device:**

Stem

**Bonnet Type:**

Packing retaining

**Maximum Operating Temp:**

150.0 degrees fahrenheit single response

**End Application:**

New construction lcs1

**Valve Operation Method:**

Air

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

2.000 inches

**Power Drive Operating Pressure:**

250.0 pounds per square inch

**Maximum Operating Pressure:**

285.0 pounds per square inch single response

**Face To Face Distance:**

10.000 inches

**Product Name:**

Two-way, reciprocating steel body globe valve with pneumatic/electrical actuator; inavy valve, diaphragm control

**Special Features:**

Application: inlet back pressure regulating/40 psi inlet; flanges iaw asme 16.5 150 lb.; disassembly distance 4"; actuator has 1/4" fpt air connection, 250 psi max.; no manual over ride; cv 45; valve travel 0.75"; type 5800 valve p/n d3230930, actuator p/n d3378425

**Material:**

Steel uns j03002 body

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0