NSN 4810-01-545-7171



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-01-545-7171 **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **End Application:** Larc v **Valve Operation Method:** Solenoid **Connection Type:** Threaded cartridge 1st end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.062 inches 1st end **Voltage In Volts And Current Type:** 24.0 dc **Product Name:** 2-way poppet valve **Special Features:** 2-way, normally closed with free reverse flow; dual lead electrical connection Material: Steel Media For Which Designed: Oil single response **Style Designator:** Err-090 **Thread Series Designator:**

Unf 1st end Shelf Life:

N/a

NSN 4810-01-545-7171

Solenoid Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0