## NSN 4810-01-558-3132

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-01-558-3132 **Thread Class:** 2b all ends **Thread Direction:** Right-hand all ends Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Minimum Operating Temp:** 30.0 degrees fahrenheit **Connection Style:** G4 gasket sea (boss) all ends **Current Rating In Amps:** 0.028 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 32 all ends **Maximum Operating Pressure:** 105.0 pounds per square inch single response **Thread Size:** 0.190 inches all ends **Voltage In Volts And Current Type:** 24.0 dc Material: Copper alloy body Media For Which Designed: Gas, inert 2nd response **Surface Treatment:** Nickel **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4810-01-558-3132

Solenoid Valve - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A046b0