

View Online at <https://aerobasegroup.com/nsn/4810-01-573-4485>

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-20.0 degrees fahrenheit

**End Application:**

N260h001 hydraulic system

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Current Rating In Amps:**

1.500

**Valve Operation Method:**

Solenoid or manual

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

5000.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

24.0 dc

**Product Name:**

Solenoid valve, normally closed 2-way 2-position

**Special Features:**

Cartridge valve in steel housing with sae 8 ports; flow 6 gpm; seal material buna n; see 4810-01-573-4483 for cartridge only, without housing

**Material:**

Steel body

**Media For Which Designed:**

Oil, hydraulic single response

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0