

View Online at <https://aerobasegroup.com/nsn/4810-01-596-9601>

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Spool

**Flow Control Device Normal Operation Position:**

Open

**Maximum Operating Temp:**

120.0 degrees celsius single response

**Minimum Operating Temp:**

-40.0 degrees celsius

**Connection Style:**

Plain (screw-in cartridge) 1st end

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded cartridge 1st end

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

210.0 bar single response

**Thread Size:**

0.375 inches 1st end

**Voltage In Volts And Current Type:**

24.0 dc

**Product Name:**

3-way 2-position direct acting spool type cartridge solenoid valve

**Special Features:**

Seal material is buna-n; for use with general purpose hydraulic fluid; electrical connector iaw iso 4400 din 43650

**Material:**

Aluminum body

**Media For Which Designed:**

Oil, hydraulic single response

**Style Designator:**

Screw-in cartridge

**Thread Series Designator:**

Bsp.PI 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0