## NSN 4810-01-604-5888

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-01-604-5888

| Flow Control Device Normal Operation Position: |
|--|
| Closed   |
| Maximum Operating Temp:                        |
| 230.0 degrees fahrenheit single response       |
| Current Rating In Amps:                        |
| 0.550  |
| Valve Operation Method:                        |
| Solenoid                                       |
| Mounting Position:                             |
| Horizontal or vertical                         |
| Valve Size:                                    |
| 0.500 inches                                   |
| Maximum Operating Pressure:                    |
| 150.0 pounds per square inch single response   |
| Voltage In Volts And Current Type:             |
| 24.0 dc  |
| Product Name:                                  |
| Energy efficient brass solenoid valves         |
| Special Features:                              |
| Valves have wire leads                         |
| Material:                                      |
| Copper alloy body                              |
| Media For Which Designed:                      |
| Oil 1st response                               |
| Style Designator:                              |
| A1a straight through flanged ends              |
| Shelf Life:                                    |
| N/a  |
| Unit Of Measure:                               |
|  |
| Demilitarization:                              |
| No   |
| Fiig:  |
| A046b0   |
|  |
|  |
|  |