

View Online at <https://aerobasegroup.com/nsn/4810-01-621-8549>

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

120.0 degrees celsius single response

**Connection Style:**

Plain (screw-in cartridge) 1st end

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded cartridge 1st end

**Mounting Position:**

Horizontal

**Thready Qty Per Inch (tpi):**

16 1st end

**Maximum Operating Pressure:**

241.0 bar single response

**Thread Size:**

0.75 inches 1st end

**Voltage In Volts And Current Type:**

24.0 dc

**Product Name:**

Solenoid operated, 2-way, normally closed, pilot-operated poppet cartridge valve

**Special Features:**

Use with general purpose hydraulic fluid; filtration iaw iso 18/16/13; coil termination iaw din 45650

**Material:**

Steel

**Media For Which Designed:**

Oil, hydraulic single response

**Style Designator:**

Screw-in cartridge

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0