

View Online at <https://aerobasegroup.com/nsn/4810-01-622-0309>

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device Normal Operation Position:

Open

Maximum Operating Temp:

120.0 degrees celsius single response

Minimum Operating Temp:

-40.0 degrees celsius

Connection Style:

Plain (screw-in cartridge) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded cartridge 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

14 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.875 inches 1st end

Voltage In Volts And Current Type:

24.0 dc

Product Name:

4-way, 2-position direct acting, spool type screw-in cartridge solenoid valve

Special Features:

Electrical connector iaw iso 4400 din 45650

Material:

Aluminum body

Media For Which Designed:

Oil, hydraulic single response

Style Designator:

Screw-in cartridge

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 electrical connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0