

View Online at <https://aerobasegroup.com/nsn/4810-01-624-7769>

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Spool

**Maximum Operating Temp:**

120.0 degrees celsius single response

**Minimum Operating Temp:**

-40.0 degrees celsius

**Connection Style:**

Plain (screw-in cartridge) 1st end

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded cartridge 1st end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

16 1st end

**Maximum Operating Pressure:**

350.0 bar single response

**Thread Size:**

0.75 inches 1st end

**Product Name:**

3-way, 2 position direct acting spool type screw-in cartridge solenoid valve

**Special Features:**

Supplied without coil; for use with general purpose hydraulic fluid suchas mil-h-5606, sae 10, sae 20, etc.

**Media For Which Designed:**

Oil, hydraulic single response

**Style Designator:**

Screw-in cartridge

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0